



Desktop Barcode Printer

# Alpha-30L

Direct Thermal



Release Note

# Copyright

©2025 TSC Auto ID Technology Co., Ltd.

The copyright in this manual, the software and firmware in the printer described are owned by TSC Auto ID Technology Co., Ltd. All rights reserved.

CG Triumvirate is a trademark of Agfa Corporation. CG Triumvirate Bold Condensed font is under license from the Monotype Corporation. Windows is a registered trademark of Microsoft Corporation.

All other trademarks are the property of their respective owners. Information in this document is subject to change without notice and does not represent a commitment on the part of TSC Auto ID Technology Co., Ltd. No part of this manual may be reproduced or transmitted in any form or by any means, for any purpose other than the purchaser's personal use, without the expressed written permission of TSC Auto ID Technology Co., Ltd.

# Contents

M2.00 Release Note .....2

# M2.00 Release Note

2025/05/21

## CPCL

- Fix CPCL Font 4 emulation output is different with Zebra
- Fix CPCL BARCODE 128 command not displaying Human readable
- Add CPCL SETVAR command to configure the printer emulation.
- Add [TCF] CPCL MULTI BARCODE command to enable/disable CPCL multi line Bar-code feature.
- Fix CPCL PAGE-WIDTH command , send two job the 1st job PAGE-WIDTH value smaller than 2nd job , the 2nd job PAGE-WIDTH value will change error
- Add CPCL new resident font "24"

## TCF

- Add [TCF] ZPL CHARACTERSET command for change international Font/Encoding

## TSPL2

- Add TSPL2 SET TIMEFORMAT Command, can set lcd time format.
- Add TSPL2 QRCODE command , support the J#,X#, Syntax item. J#:Barcode justification. (1 to 9); X#:Limit size of barcode area.
- Add TSPL2 SET RESPONSE command, this command can response issue automatically {Status,#####,ID}.
- Add TSPL2 NET WEBPASSWORD CLEAR command, it's can cancel the web "Welcome to first time" setting.
- Add Vertical DPI function
- Add TSPL2 SET DATAFORMAT Command, can set lcd date format..

## WIFI

- Modify Wi-Fi Password can use special characters
- Add WiFi Roaming Trigger/Delta setting menus.
- Modify web page could set 9100 port timeout. (Default: 0, no timeout)

## ZPL2

- Fix ZPL2 support 0x1F as delimiter
- Fix ZPL2 cannot print ZPL Cyrillic characters
- Add ZPL2 ^FO command, suport Justification Function
- Fix ZPL2 ^BR command, cannot be rotated by ^FW command
- Fix ZPL2 ^LR command, label reverse print field when using ^FN field number command.
- Fix ZPL2 ^BQ command, position error when using ^FT command.
- Fix ZPL2 draw font will crash when setting large font size.
- Fix ZPL2 ^ADR command causes freezing.

